

---

## Subject index

---

- 1.6, factor for converting from logit to  
probit, 86, 118, 131
- 100,000 iterations, why we do not  
recommend, 369
- 2 standard deviations, scaling by, 56–57
- 2.8 standard errors for power calculation,  
441
- 5 ways to write the same model, 262–265
- 55,000 residents desperately need your  
help, 23–26
- 6 quick tips, 547–549
- 8 schools, 430–434
  
- ability parameter, in item-response model,  
315–320
- abline(), 353, 520
- Academy awards, 133
- accessing the simulations from a Bugs fit,  
358
- AD Model Builder, multilevel modeling in,  
572–573
- adding a predictor can increase the  
residual variance, 480–481
- additivity, 46
- adjusted parameters, 382, 420, 422  
compared to raw parameters, 423
- adjusted R, 475
- Advanced Placement exams, 463–464
- age guessing, 299
- age, as regression input, 66, 67
- Akaike information criterion (AIC), 105,  
525–527
- aliasing, a form of nonidentifiability, 318,  
321
- American Indians, 340
- analysis of covariance, 496–498
- analysis of variance (ANOVA), 487–502
  - additive data decomposition, 488
  - balance, 489
  - classical, 487–490
  - contrasts, 462–466, 496–498
  - degrees of freedom, 488, 499
  - F-test, 489
  - generalized linear models, 491
  - graphical display, 492–495, 497, 499,  
500
  - mean square, 489
  - method of summarizing a multilevel  
model, 492–494
  - model comparison and, 489
  - multilevel models and, 490–502
  - nested designs, 496
  - sum of squares, 488
  - unbalanced designs, 496
- analytic calculations and simulation, 148
- Annenberg Election Survey, 311
- apply(), 44, 353, 477
- array(), 308
- arsenic, *see* wells
- as.bugs(), 413
- as.bugs.array(), 400
- as.vector(), 348
- attach.bugs(), 305, 352, 358
- augmented data
  - multilevel model, 397
  - regression with prior information, 393
- autoregression, 163–165
- available-case analysis, 532
- average causal effect, definition, 173
- average predictive comparison, *see*  
predictive comparison
- axes of graphs, 553
  
- B-K plot, 312, 313, 321
- balance, *see* causal inference
- Bangladesh, *see* wells
- basement, 254
- Bayesian inference, 142, 276, 345–348,  
392–414
  - calibration, 433
  - censored data, 405–408
  - classical regression, 392
  - debugging, 434
  - exchangeability, 347
  - Gibbs sampler, 397–402
  - informal, 143
  - informative prior distribution,  
392–393, 427–434
  - Metropolis algorithm, 408–409
  - multilevel model, 393–402, 413
  - picture, 395, 396
  - prior distribution, 427–434
    - variance parameters, 432–434,  
499–501

- separation in logistic regression, 104
  - social networks model, 409–413
- beauty and teaching evaluations, 51
- before-after graph, 555
- behavioral learning experiment, 515–524
- beta-binomial model, 321
- binary data and count data, 117
- binary outcomes, 79
- binned residual plot, 97–101, 105, 559
- binomial distribution, 16
  - bounding trick in Bugs, 382
  - compared to Poisson, 112
- binomial-normal model, 321
- births, 27, 137–139
- black box, 190
- bounding parameters in Bugs, 383
- bounding trick for binomial model in Bugs, 382
- brlr package, 104
- broken windows, 325
- Bugs, 11, 305, 345–386, 567, 573
  - bounding parameters, 383
  - bounding trick for binomial model, 382
  - brute force, why we do not recommend, 369
  - calling from R, 350–352
  - censored data, 405–406
  - classical regression, 360
  - compared to lmer(), 386
  - compared to R, 399–402
  - compiling, 416
  - complete-pooling model, 360
  - confidence-building, 415–417
  - current problems with, 417
  - data, 350, 356, 416
  - data, parameters, and derived quantities, 366–369
  - dbin(), 381
  - dcat(), 383
  - debugging, 415–417
  - derived quantities, 367
  - detailed example, 348–359
  - dgamma(), 430
  - dlnorm(), 383
  - dlogis(), 384
  - dmnorm(), 376
  - dnorm(), 353, 354
  - dt(), 372, 384
  - dunif(), 355
  - dwish(), 377
  - each object can be defined at most once, 368
  - equals(), 384, 405
  - example of graphical output, 351
  - example of slow convergence, 421
  - example of tabular output, 351
  - examples, 353
  - fake-data simulation, 363–365
  - finding errors in a model, 373
  - general principles, 366–369
  - group-level model, 354
  - help, 353, 373, 565
  - I(), 383, 384, 405
  - individual-level model, 353
  - initial values, 350, 356, 369–370, 416
  - inprod(), 361, 378, 379
  - interpreting inferences from fitted model, 352
  - inverse(), 377
  - inverse-variance parameterization, 354, 368
  - knowing when to give up, 419
  - latent data for generalized linear models, 384
  - linear transformation to speed convergence, 419–427
  - logistic regression, 381–382
    - latent-data formulation, 384
  - logit(), 381
  - looping indexes, 353, 367
  - max(), 381
  - mean(), 382
  - min(), 381
  - missing data, 367, 529
  - model as specifications, not instructions, 368
  - model too big for, 336
  - modeled data and parameters, 366, 367
  - multilevel model, 375–386
    - logistic, 381–382
    - non-nested, 380–382
    - Poisson, 382
    - varying intercepts and slopes, 375–379
  - multiple group-level predictors, 379–380
  - multiple varying coefficients, 378
  - n.thin, 518
  - nested subscripts, 372
  - no overwriting in model, 368
  - no-pooling model, 360
  - non-nested model, 380–381
  - noninformative prior distribution, 355
  - nonlinear and nonadditive models, 371
  - number of iterations and sequences, 356–358, 369
  - open-ended modeling, 370–372
  - ordered categorical regression, 383
  - overdispersed Poisson regression, 382

- parameters, 350, 356
- postprocessing inferences in R, 359
- pow(), 355
- practical advice, 357, 369–370, 415–434, 547–549
- prediction, 361–363
- prior distribution, 354
- $\hat{R}$ , 358, 369
- raw (unscaled) parameters, 377
- redundant parameters, 419–427
- replicated data for predictive checking, 518
- robit regression, 384
- scaled inverse-Wishart model, 376–380
- sd(), 460
- simple multilevel model, 350
- slow with large datasets, 418
- stochastic learning model
  - logarithmic link, 521
  - logistic link, 517
  - multilevel, 522–524
- thinning, 418
- too slow for looping in power
  - calculation, 451
- unequal variances, 371–372
- unmodeled data and parameters, 366, 367, 378
- varying-intercept model, 350, 361
- varying-intercept, varying-slope model, 375–379
  - group-level predictors, 379–380
  - modeling the correlation, 376
  - no correlation, 375
  - scaled inverse-Wishart, 376
  - why you should learn Bugs, 345
- Wishart model, 376–380
- bugs(), 350, 565, 567
- building generalized linear models, 125–127
- building regression models, 68–73
- c(), 350
- calibration
  - Bayesian inference, 433
  - plot, 309, 558
- calling Bugs from R, 350–352
- Caltech, 332
- cancer and nutrients, 294
- categorical variables as regression inputs, 66
- Cauchy distribution, 428, 430
- causal inference, 95, 167–198, 549
  - average causal effect, 173, 180, 205
  - balance, 181, 184–186, 199–204, 208, 209, 212
  - plot, 202, 229
- causes of an effect, 187
- confounding covariate, 169, 176, 181, 184, 196, 200, 202–203, 207, 212–213, 215
- constructed observational study, 210, 230, 231
- continuous treatment, 177
- controlling for post-treatment variable, don't do it, 177, 187–194, 227, 229
- counterfactual, 170, 173, 184, 185, 188, 201, 206, 218
- definition, 170
- difference-in-differences, 228, 231
- direct and indirect effects, 191–194
- effect of causes, 187
- effect of the treatment on the controls and treated, 205, 206, 211
- exclusion restriction, 216–218
- experiment, *see* randomized experiment
- external validity, 174
- fixed effects, 231
- fundamental problem, 171–172, 191
- hypothetical intervention, 187
- ignorability, 182–184, 186, 207, 212, 216–217, 225, 228, 231, 232
- infinite regress of causation, 187
- instrumental variables, 215–226, 230–231, 233
  - assumptions, 216–218, 220–221, 225–226, 233
  - derivation, 218–221
  - identifiability, 220–221, 224
  - multilevel model, 509–511
  - standard error, 222
  - two-stage least squares, 221
  - Wald estimate, 219, 221
  - weak instrument, 225
- intent-to-treat (ITT) effect, 216, 219, 220, 222
- internal validity, 174
- local average treatment effect (LATE), 219–220, 229, 233
- mapping your study to an ideal randomized experiment, 187–188
- matching, 206–212
  - model checking, 208
  - nearest-neighbor, 207
  - propensity score, 230
  - R packages for, 230
- model extrapolation, 169, 185, 201, 209, 213
- monotonicity, 216–217

- multilevel model, 178, 210, 212, 227–228, 503–512
- multiple treatments, 177, 186, 187
- natural experiment, 187, 225
- nonignorable assignment mechanism, 183
- observational study, 172, 181–188
  - design of, 437
- overlap, 184–186, 199–204, 209, 212–215
- poststratification, 178, 181, 206
- potential outcome, 168, 170, 171, 183, 186, 189, 191, 219
  - close substitutes, 171–172
- predictive comparison, 167, 168
- principal stratification, 192
- propensity score matching, 207–210, 230, 232
  - assumptions, 207
  - model checking, 208
  - R packages for, 230
  - standard errors, 212
- propensity score weighting, 211, 229
- randomized encouragement, 216
- randomized experiment, 171–181, 183
  - completely randomized, 175, 182, 183
  - design of, 437
  - paired comparisons, 175
  - randomized blocks, 175
- regression, 167–198
- regression discontinuity, 212–215, 232
- selection bias, 168
- selection model, 231
- selection on observables, 183
- sensitivity analysis, 231
- simultaneous causality, a meaningless concept?, 188
- structural equation model, 226
- subclassification, 204–207, 210–211, 229
- support of the data, 169
- SUTVA, stable unit treatment value assumption, 178
- treatment interaction, 178–180, 189, 205, 214–215
- treatment variable, definition, 186
  - weighting, 205
- `cbind()`, 43, 146, 157, 361, 529
- CD4, 249, 277, 373
- censored data, 402–408
  - Bayesian inference, 405–408
  - Bugs, 405–406
  - Gibbs sampler, 406–408
  - imputation for, 540–541
  - likelihood, 404
  - maximum likelihood, 404–405
  - naive regression estimates, 403–404
  - picture, 541
  - R, 404–408
- Census, 277, 301, 308
- centering, 55–57, 419, 464–466
  - changes the correlation of group-level intercepts and slopes, 288–289
  - interactions and, 93
  - non-nested model, 292
- Central Limit Theorem, 13–14, 27
  - regression coefficients, 14
- chick brains, magnetic fields and, 481–484
- child care, 189–193, 201, 224
- child support enforcement in cities, 237–241
- children with HIV, 249, 443–447
- children’s test scores, 31–51, 55–57
- classical models for regression coefficients, 293
- classical regression, as a special case of multilevel modeling, 258
- cluster sampling, 437, 447–449
- clustered data, 237–241
- cockroaches, 126–127, 161–163
- `coef()`, 43, 156, 260, 267, 280, 352
- coin flipping, patterns in, 554
- collinearity, 68, 255, 393, *see also* identifiability
- `colMeans()`, 520
- colochos, canasta de, vii, xxii
- `colors()`, 43
- `colSums()`, 411
- combining inferences from multiple imputations, 542
- combining separate local regressions, 263
- comparing two surveys, 442
- comparisons, graphs as, 552–553
- compiling Bugs, 416
- complete pooling, 247, 252–259, 270, 348
  - Bugs model, 360
  - problems, 256
  - special case of multilevel modeling, 258
- complete-case analysis, 531
- compound models
  - imputing a variable that can be positive or zero, 537–538
  - simulation of, 150–151, 537–538
- computer display, 565, 566
- computing, 9–11, 547, 565–574
  - debugging, 415–417
  - instead of matrix algebra, 8
  - multilevel models, 345–434
  - practical advice, 415–434
- confidence intervals, 18–20

- continuous data, 18
  - discrete data, 18
  - proportions, 18
- confidence-building, 415–417
- confounding covariate, 169, 176, 181, 184, 196, 200, 202–203, 207, 212–213, 215
- congressional elections, 76, 144–148, 197, 213, 233
- conjunctive item-response or ideal-point model, 319
- connect times on the web, 492–493
- Connecticut, what’s the matter with, 310–314
- constant term, 251, 349
- constraining a batch of coefficients to sum to zero, 326
- constructed observational study, 210
- constructive choice models, 127–131
- contextual effect, 481
- continuous and discrete predictors, 66
- continuous probability simulation, 152
- contrasts, 462–466
  - analysis of variance, 496–498
  - computing in R, 464
- convergence of iterative simulations
  - monitoring, 352
  - pictures, 357
- correlation, 57–59, 265, 389
  - coefficient estimates, 40
  - graph, 340
  - group-level intercepts and slopes, 279, 287–289
  - individual-level variables and group-level errors, 481
  - modeling in Bugs, 376–380
  - scaled inverse-Wishart model, 287
- cost-benefit analysis, 128, 153, 454–455
- costs and benefits of multilevel modeling, 246–247
- count data and binary data, 117
- counterfactual, 170, 173, 184, 185, 188, 201, 206, *see also* potential outcome
- counterfactual and predictive
  - interpretations of regression, 34
- covariance, *see* correlation
- coverage of confidence intervals, 156
- cows, 196
- $C_p$ , 527
- curve(), 43, 353
- cutpoints, for ordered logit or probit, 119–120, 332
  - estimating in Bugs, 383
- data cleaning, for social networks survey, 333
- data for examples, 11
- data matrix, 37, 238, 239
  - group-level, 239, 240, 243
  - imputation, 541
  - individual-level, 239, 243
  - non-nested data, 243
- data model, 347
- data reduction, 209
- data sent to Bugs, 350, 356, 416
- data subsetting, 326, 357, 547
  - speeding computation, 418
- data.frame(), 48, 140, 452, 535
- dbin(), 381
- dcat(), 383
- death penalty, 19, 116, 243–244, 320–321, 540–541
- debugging, 415–417, 434
  - diagram of general strategy, 416
- decision analysis, well-switching example, 127–131
- default line in graph, 556, 560
- defaults in R functions, 452
- degree distribution, estimated for men and women, 337
- degrees of freedom, 41, 372, 488
  - inverse-Wishart distribution, 286
- Democrats and Republicans, 310–314
- dependent variable, *see* outcome
- derived quantities, 366, 367
- design of sampling and experiments, 437–455
- details in graphs, 560
- deterministic or random imputation, 534, 537
- deterministic part of a regression model, 31
- deviance, 100, 105, 113, 524–526
- deviance information criterion (DIC), 105, 525–527
  - instability in computation of, 526
- dgamma(), 430
- diagnostics
  - external validation, 48
  - residuals, 40, 47, 97–101
  - simulation-based, 155–166, 513–524
- diarrhea, zinc, and HIV, 443–447
- difference-in-differences estimation, 228, 231
- difficulty parameter, in item-response model, 315–320
- dim(), 147
- dimnames(), 400
- discrepancy variable, 513
- discrete and continuous predictors, 66, 107
- discrete probability simulation, 152

- discrimination parameter, in item-response model, 316
- disjunctive item, 319
- display(), 38–39, 565
- distance to the nearest safe well, 88
- distribution, 13–16
- binomial, 16
    - bounding trick in Bugs, 382
  - Cauchy, 428, 430
  - folded noncentral t, 428
  - gamma, 335
  - log=TRUE option in R, 405
  - logistic, 85
    - Bugs, 384
  - lognormal, 15, 383
  - multivariate normal, 15
  - negative binomial, 115, 336
  - normal, 13–15, 263
    - computing in R, 405
    - truncated, 407
  - Poisson, 16, 110–116, 335
  - scaled inverse-Wishart, 284–287, 376–380
  - t, 124, 372, 428
  - truncated normal, 407
  - Wishart, 284–287, 298, 376–380
- divide by 4 rule, for interpreting logistic regression, 82
- dividing by two standard deviations, 56–57
- dlnorm(), 383
- dlogis(), 384
- dmnorm(), 376
- dnorm(), 353, 354, 404
- dog experiment, 515–524
  - model comparison, 526
  - observed and replicated data, 516, 523
- Douglas, William, 318
- dt(), 372, 384
- dummy variable, *see* indicator
- dunif(), 355
- dwish(), 377
- dynamic graphics, 563
- earnings
  - height and, 50, 53–54, 75, 126, 287, 290–292
  - logarithmic models, 59–65
  - mixed discrete/continuous data, 126
- econometrics and biostatistics, 231
- education as categorical input variable, 95
- educational children’s television programs, *see* Electric Company *and* Sesame Street
- educational testing, 317, 430–434
- effect size, why more important than sample size, 439
- effective sample size, 352
- elasticity, 64, 76
- election forecasting, graphs of, 557, 562
- election fraud, 23–26
- Electric Company experiment, 174–186
  - graph of data, 552
  - multilevel model, 503–505
- Emacs, 565
- equal variance of errors, 46
- equals(), 384, 405
- Erdos-Renyi model, 334
- error rate, 99
- errors, distinguished from residuals, 387
- exam scores, actual vs. guessed, 558, 559
- examples, data for, 11
- exchangeability and prior distribution, 347
- exclusion restriction, *see* causal inference, instrumental variables, assumptions
- expected(), 123
- experiment, *see* causal inference, randomized experiment
- experimental design, 437–455
- experimental economics, 331
- explained variance, *see*  $R^2$
- exploratory data analysis, 551
- exposure, in Poisson model, 111–113
- expression(), 148, 353
- external validation, 48
  - election polls, 309
- external validity, 174
- F-test, 489
- factor, 68
- factor analysis, 296
- factor(), 255, 349
- fake-data simulation, 50, 155–158
  - Bayesian inference and, 434
  - checking coverage of intervals, 365
  - multilevel model, 363–365
  - residual plots, 157–158
  - sample size and power calculations, 449–454
  - using Bugs, 363–365
- feeling thermometer, 86
- figure skaters, 248
- finite-population variance, 459–462, 499
- analysis of variance (ANOVA), 491
  - Bugs, 460
  - graph, 461
  - unmodeled coefficients, 462
- fit many models, 547
- fitted(), 158
- fitting multilevel models, 259–262, 345–434
- fitting the wrong model, 165
- fixed effects, 231, 244–246, 259, 261

- finite-population inferences and, 461
  - many definitions, 245, 248
  - R, 260
  - why we avoid the term, 2, 226–228, 245
- fixef(), 260, 280
- flight-simulator experiment, 289–290, 297, 464–466
  - analysis of variance, 488
  - Bugs model, 380
  - superpopulation and finite-population variance, 459–460
- folded noncentral t distribution, 428
- forecasting elections, 294–296
- Fragile Families study, 238
- function(), 350, 401
- functions in R, 139, 147, 151, 404, 534, 535
- fundamental problem of causal inference, 171–172, 191
  
- gain scores, 177, 195
- Gallup Report, 560
- GAMM package, 567
- gamma distribution, 335
- generalized additive model, 298, 567
- generalized estimating equations, 248
- generalized linear model, 109–133
  - analysis of variance (ANOVA), 491, 493–494
  - binomial, 116–117
  - building, 125–127
  - cutpoints, 119–120
  - deviance, 100, 105, 113
  - latent-data formulation, 384
  - logistic, 79–108
  - logistic-binomial, 109, 116–117
  - multilevel, 325–342
  - multinomial logit and probit, 110, 119–124
  - negative binomial, 115
  - ordered logit, 119–124
    - Bugs, 383
    - multilevel, 331–332
  - others, 127
  - Poisson, 109–116
    - Bugs, 382
    - compared to binomial, 112
    - exposure, 111–113
    - overdispersion, 382
  - prediction, 272
  - predictive comparisons, 466–473
  - probit, 109, 118–119
  - probit or logit, 118
  - robit as robust alternative to logit and probit, 124–125
  - robust, 110
  - simulation, 148–151
  - thresholds, 119–120
- Gibbs sampler, 385, 397–402
  - censored data, 406–408
  - linear transformation to speed convergence, 419–427
  - model building and, 402
  - multilevel model, 398–402
  - picture, 398
  - programming in R, 399–402, 412
  - redundant parameters, 419–427
  - slow convergence, 424
  - social networks model, 410
  - updating functions in R, 399–402
- glm(), 79, 110, 565
- global variables in R, 400, 412
- goodness-of-fit, *see* model checking
- grades, predicting, 157
- graphics, 42–45, 548, 551–563
  - comparisons, 552–553
  - general advice, 562
  - instead of tables, 328, 337
  - jittering, 32
  - no single graph does it all, 552–553
  - plotting regression model, 337, 341
  - plotting symbols, 555
  - R, 562
  - scatterplot with regression lines superimposed, 35, 42–45
  - shape of the plotting region, 556
  - showing fitted models, 551, 553
  - symbols and auxiliary lines, 554
  - theory of, 562
  - why, 551
- group, 261
- group indicators, 264
- group- and individual-level data matrices, 239, 243
  - imputation, 541
- group-level predictors, 265–269, 271
  - along with group indicators, 269, 293, 463–464, 498
  - Bugs model, 361
  - varying-intercept, varying-slope models, 280
- group-level standard deviation, 270
- guessing ages, 299
- guessing, in item-response model, 319
  
- handedness, 66
- hard constraint, 257
- hazard regression, 298
- height, 139
  - earnings and, 50, 53–54, 75, 126, 287, 290–292

- logarithmic models, 59–65
  - mixture model for, 14
  - parents and children, 58
  - weight and, 41, 74, 402–408
- help in Bugs, 565
- help in R, 405, 565, 567
- heteroscedasticity (unequal variances), 297
- hett package for robust regression, 110, 124, 133, 567
- hist(), 137, 536, 562
- histograms, 561
- HLM, multilevel modeling in, 573
- holding other predictors constant,
  - difficulty of, 34
- homeless people, 333
- hot-deck imputation, 538
- how many groups, 275–276
- how many observations per group, 275–276
- how many x's survey, 332–342
- hyperparameter, 1, 258
- hypothesis testing, 20–26
- I(), 215, 383, 384, 405, 538
- ideal-point model, 314–321
  - multilevel, 316
  - picture, 315
  - redundant parameters in Bugs, 426
  - two-dimensional, 319
- identifiability, 419, 420
  - Bayesian regression and, 393
  - categorized predictors and, 68
  - causal inference, 170
  - constant term in non-nested models, 381
  - ideal-point model, 318
  - instrumental variables, 220–221, 224
  - item-response model, 315
  - likelihood and, 392
  - linear regression, 68
  - logistic regression, 86, 104, 107
  - social networks model, 336
- ifelse(), 126, 150, 384, 403, 534
- ignorability, 182–184, 186, 231, 530, 542,
  - see also* causal inference
- imbalance, *see* causal inference, balance
- imputation, *see* missing data
- impute(), 535
- income and voting, 79–84, 105, 107, 310–314
- incremental cost-effectiveness ratio, 153
- incumbency, 197, 233
- independence of errors, 46
- independent variable, *see* input variable
- index number, don't graph by, 553
- index variable, 67, 238, 252
  - creating in R, 348
  - non-nested models, 289
- indicator variable, 67, 238, 244–246, 255
  - default, reference, or baseline condition, 68
- individual- and group-level data matrices, 239, 243
  - imputation, 541
- Infant Health and Development Program,
  - see* child care
- inference, *see* statistical inference
- informative prior distribution, 392–393
- initial values sent to Bugs, 350, 356, 369–370, 416
  - restricted parameter space, 384
- inprod(), 361, 378, 379
- input variables, as distinguished from predictors, 37, 466
- install.packages(), 567
- instrumental variables, *see* causal inference
- interactions, 34–36, 242, 453
  - centering the input variables, 93
  - graphing, 36, 94, 313
  - logistic regression, 92–96
  - predictive comparisons and, 469
  - sample size and, 438
  - treatment effects, 178–180, 189, 205
  - varying slopes as example of, 282–283
  - when to look for, 36
- intercept, 33, 35, *see* varying intercepts and slopes
- intermediate outcome, *see* causal inference, controlling for post-treatment variable
- internal validity, 174
- interpreting regression coefficients, *see* linear regression, logistic regression, generalized linear model, *and* multilevel model
- interquartile range (IQR), 70
- intraclass correlation (ICC), 258, 448
- inverse variance, used in `dnorm()` in Bugs, 354–355
- inverse(), 377
- inverse-gamma distribution, why we do not use as prior distribution for variance parameters, 430–434
- inverse-logit function, 80
- invlogit(), 149
- item-response model, 314–321
  - guessing, 319
  - multilevel, 316
  - picture, 315, 317
  - redundant parameters in Bugs, 426
  - two-dimensional, 319
- iterative regression imputation, 539
- iterative simulation, 408–409



- Jacobian for nonlinear transformations, 409, 430
- Jaycees, 334, 335, 340
- `jitter.binary()`, 89
- jittering, 32, 554
- knowing when to give up, 419
- Lac Qui Parle County, 253
- large regression with correlated errors, 265
- latent-data formulation for logistic regression, 85–86, 120
- latin square, 292, 297, 497–501
- Latinos, hypothetical survey of, 454
- least squares, 39, 387–390
  - augmented data and multilevel model, 396–397
  - weighted, 389
- legislative redistricting, 555
- `length()`, 157
- level, 68
- `lgamma()`, 411
- `library()`, 567
- likelihood, 347, 387–414
  - censored data, 404
  - generalized linear model, 389–390
  - inferential uncertainty and simulation, 392
  - logistic regression, 389
  - picture, 390, 391, 395, 396
  - Poisson regression, 390
  - social networks model, 409–413
  - surface, 390–392
- linear predictor, 79, 305
- linear regression, 31–77, 387–390
  - assumptions, 45–47
  - Bayesian inference, 346
  - binary predictor, 31
  - Bugs model, 360
  - compared to principal component line, 57–58
  - continuous predictor, 32
  - correlation and, 57–59
  - counterfactual interpretation, 34
  - diagnostics, 45–47
  - displaying several, 73–74
  - fitting in R, 38–39
  - general principles for building models, 69
  - inferential uncertainty, 40
  - interactions, 34–36
  - interpreting coefficients, 33–34
    - interactions, 35–36
  - least squares, 39
  - matrix notation, 388
  - missing-data imputation, 533–538
  - multiple predictors, 32–34
  - notation, 37–38
  - one predictor, 31–32
  - picture of matrix, 37
  - prediction, 47–49, 70–73, 272
  - predictive interpretation, 34
  - sample size and power calculations, 446, 451
  - simulation, 140–148
  - standard error, 40
  - statistical inference, 37–42
  - transformation, 53–77
  - validation, 47–49
- linear transformation, 14, 53–54, 88, 95, 122, 294
  - centering a batch of multilevel coefficients, 464–466
  - prior distribution and, 355
  - speeding convergence of Gibbs sampler, 419–427
- linearity, 46
- link function, 109
- `list()`, 143, 350
- `lm()`, 38–39, 402, 565
- `lmer()`, 259–262, 266, 267, 277, 566, 573
  - compared to Bugs, 386
  - limitations, 262, 304, 345
  - logistic regression, 302
  - non-nested model, 289
  - six quick examples, 568–569
  - varying intercepts and slopes, 279–289
- local average treatment effect (LATE), 219–220, 229, 233
- `log()`, 59
- log-log model, 64
- `log10()`, 61
- logarithmic transformation, 59–65, 98, 252
  - even when not necessary, 65
  - interpreting regression coefficients, 60
  - interpreting variance parameters, 327
  - picture, 60
  - why we usually don't use base 10, 60–61
- logistic distribution, 85
  - Bugs, 384
  - close to normal with standard deviation 1.6, 86, 118, 131
- logistic regression, 79–108
  - binned residual plot, 105
  - Bugs, 381–382
    - latent-data formulation, 384
  - choice models in one and multiple dimensions, 128–131
  - compared to probit, 118, 129
  - computing using `lmer()`, 302
  - deviance, 100, 105

- divide by 4 rule for interpreting
  - coefficients, 82
- graph of coefficient estimates, 306
- graphs of data and fitted curves, 307
- ideal-point model, 314–320
- identifiability, 86, 104, 107
- inference, 83
- interactions, 92–96
- interpreting coefficients, 81–84, 89
- item-response (Rasch) model, 314–320
- latent-data formulation, 85–86, 384
- logit and logit<sup>-1</sup> functions, 80
- missing-data imputation, 533–538
- multilevel, 301–323
  - Bugs, 381–382
  - formula, 302, 303
  - graphing, 304–310
  - interpreting coefficients, 304
  - non-nested, 302–304, 320–321
  - overdispersion, 320–321
- odds ratios, 82–83
- pictures, 80
- plotting data and fitted curve, 80, 84
- predictive comparisons, 81
- prediction, 272
- predictive comparisons, 101–104, 466–473
- propensity score, 207–208
- separation, 104, 107
- simulation, 148
- standard error, 83
- two predictors, 90–92
- varying-intercept, varying-slope model, 310–314
  - wells in Bangladesh, 86–92
- logistic-binomial model, 109, 116–117
  - overdispersion, 116
- logit, *see* logistic regression
- logit(), 381
- lognormal distribution, 15, 383
- looping indexes in Bugs, 353, 366, 367
- looping, for power calculation, 452
- lowess, 298
- lurking variable, 169
  
- magnetic fields and brain functioning, 481–484
- Mahalanobis distance, 207
- many predictors, multilevel models for, 293–296
- maps, 556–557
- Markov chain Monte Carlo (MCMC), 408–409
- MASS package, 122, 567, 573
- matching, 206–212
  - missing-data imputation, 538
  - propensity score, 207–210, 232
  - R packages for, 230
- matching(), 208
- maternal IQ, 32
- matrix notation, 37–38, 284–287
- matrix of predictors
  - group-level, 252
  - individual-level, 251
- matrix of simulations, 146, 149, 353, 358
- Matrix package, 259, 566
- max(), 381
- maximum likelihood, 388–390
  - censored data, 404–405
  - generalized linear model, 389–390
  - logistic regression, 389
- MCMCpack, 567
- mean(), 56, 359, 382, 477
- mediator, *see* causal inference, controlling for post-treatment variable
- men and women, 337
- mesquite bushes, 68–73
- meta-analysis, 386, 438
- Metropolis algorithm, 385, 408–409
  - picture, 408
  - social networks model, 410
- midterm and final exams, 157
- millet crop, 292
- millimeters, inches, and miles, 53
- min(), 381
- missing at random (MAR), 530, 542
  - impossibility of verifying, 531
- missing completely at random (MCAR), 530
- missing data in R and Bugs, 529
- missing not at random (MNAR), 530
- missing values, not allowed in unmodeled data, 416, 529
- missing-data imputation, 333, 529–543
  - available-case analysis, 532
  - Bugs, 367
  - complete-case analysis, 531
  - congressional elections, 145
  - deterministic or random, 534, 537
  - iterative, 539
  - many variables, 539–540
  - matching, 538
  - model-based, 540–541
  - models, 530–531
  - multilevel data structures, 541
  - one variable, 533–538
  - simple methods, 531–533
  - topcoding, 534
- Mississippi, as poor state, 313
- mixed discrete/continuous data, 126, 537
- mixed effects, *see* random effects

- MLWin, multilevel modeling in, 573
- mnp package, 110
- model checking, *see* posterior predictive checks *and* residuals
  - using simulation, 158–165, 513–524
- model comparison, 524–526
- model extrapolation, 169, 185, 201, 209, 213
- model-based imputation, 540–541
- modeled data and parameters, 367
- modeling the coefficients of a large regression model, 264
- monotonicity, *see* causal inference, instrumental variables, assumptions
- month of arrest, 21, 331
- more than two varying coefficients, 285
- mothers and children, 31–51, 55–57
- motivations for multilevel modeling, 6–8, 246–247
- mtext(), 520
- multilevel model, 1, 237–342, 463
  - alternative to selecting regression predictors, 294
  - analysis of variance (ANOVA), 490–502
  - assumptions, 247
  - Bayesian inference, 393
  - Bayesian perspective, 346
  - building, 293–296
    - Gibbs sampler, 402
  - building from classical regression, 270
  - causal inference, 503–512
  - combining regression inputs, 293–296
  - compared to classical regression, 463
  - comparison to simpler methods, 310
  - complexity, 246
  - computing, 345–434
  - equivalent sample size, 258, 268
  - factor analysis and, 296
  - fake-data simulation, 363–365
  - fitting in Bugs, 345–386
  - fitting in R, Stata, SAS, and other software, 568
  - fitting using lmer(), 259–262
  - five ways to write, 262–265
  - generalized linear model, 325–342
  - Gibbs sampler, 398–402
    - programming in R, 399–402
  - graphing, 304–310
  - group-level predictors, 265–269, 568
  - group-level variance, superpopulation and finite-population, 459–462
  - how many groups needed, 275–276
  - how many observations per group needed, 275–276
- imputation at different levels, 541
- inference for groups with no data, 306
- instead of comparing significance levels, 482
- instrumental variables, 509–511
- interpreting coefficients, 268
- least squares with augmented data, 396–397
- logistic regression, 301–323, 568
  - Bugs, 425
  - computing using lmer(), 302
  - non-nested, 302–304, 320–321
  - overdispersion, 320–321
- matrix notation, 284
- negative binomial, 332–342
- non-nested, 289–293, 569
  - Bugs, 380–382, 424
  - identifiability of constant term, 381
  - negative binomial, 332–342
  - redundant parameters, 421–423
- notation, 251–252
- ordered logistic regression, 331–332
- plot of group-level estimates and fitted regression line, 266, 307
- Poisson (overdispersed), 332–342, 382, 568
- pooling, 252–259
- prediction, 272–275, 361–363
- predictive comparisons, 470
- prior distribution for variance parameters, 427–434, 499–501
- $R^2$ , 473–477
- redundant parameters, 420
- sample size and power calculations, 447–454
- six quick examples, 568–569
- small number of groups, 431–432, 461
- statistical significance, 271
- summarizing and displaying, 261
- understanding and summarizing, 457–486
- variance parameters, 480–481
- varying intercepts and slopes, 279–289, 568
- varying slopes without varying intercepts, 283–284
- varying the number of groups, 330
- multilevel modeling
  - costs and benefits, 9, 246–247
  - motivations, 6–8, 246
  - when most effective, 270
- multilevel structures, 237–249
  - data matrix, 238–240, 243
  - imputation, 541
- multinomial logit and probit models, 110, 119–124

- storable votes, 120–124
- multiple chains, necessary to monitor
  - mixing, 356–358
- multiple comparisons, why we do not worry about, 22, 484–485
- multiple imputation, combining inferences, 542
- multiplicative model, 59
- multivariate imputation, 539–540
- multivariate normal distribution, 15
- mvrnorm(), 143
  
- n.chains, number of chains when running Bugs, 356–358, 369
- n.eff, effective sample size of Bugs fit, 352, 358
- n.iter, number of iterations when running Bugs, 356–358, 369
- n.sims, 143
- n.thin option in Bugs, 518
- NA, missing value in R and Bugs, 50, 362, 529
- naming inputs, 62
- National Election Study, 73, 311, 342, 385
- National Longitudinal Survey of Youth, 210
- National Supported Work, 231
- natural log, 60–61
- ncol(), 361, 519
- negative binomial distribution, 115, 336
  - multilevel model, 332–342
- neighborhoods and crime, 325, 342
- nested subscripts in Bugs, 372
- networks, 297, 333
- New York City schools, 458–459
- Newcomb’s speed of light data, 159
- Nicoles, 333, 335, 340
- nmatch package, 230
- no data, multilevel inference for groups with, 306
- no pooling, 247, 252–259, 270, 349
  - Bugs model, 360
  - overestimates between-group variation, 253
  - picture, 253
  - problems, 256
  - special case of multilevel modeling, 258
- non-nested models, 241–244, 248–249, 289–293
  - Bugs, 380–381
  - varying intercepts and slopes, 291
  - where to put the intercept or constant term, 381
- nonidentifiability, *see* identifiability
- noninformative prior distribution, 347, 355
  - Bugs, 354, 355
- nonlinear prediction, 147
- nonparametric regression, 297
- normal distribution, 13–15, 263
  - computing in R, 405
  - estimated regression coefficients, 15, 40, 83
  - inverse-variance parameterization in Bugs, 354–355
  - regression errors, 46
  - truncated, 407
- notation, 263
  - capital letters for matrices, lowercase for vectors and scalars, 167, 252, 376, 383
  - cluster sampling, 447
  - linear regression, 37–38
  - multilevel model, 251–252
  - parameters and probability distributions, 13
  - varying intercepts and slopes, 284
- nrow(), 519
- number of iterations when running Bugs, 356–358, 369
- number of observations and groups needed, 275–276, 278
- number of sequences when running Bugs, 356–358, 369
- numerical optimization in R, 405
- nutrients and cancer, 294
- NYPD stops, *see* police stops
  
- O’Connor, Sandra Day, 318
- observational study, *see* causal inference
- odds ratios and logistic regression, 82–83
- offset, in Poisson regression, 112, 326, 382
- Ohio, as intermediate state, 313
- Olympics, 248, 485
- omitted variable, 169
- omniscience, 195
- one-way analysis of variance, 494
- open-ended modeling in Bugs, 370–372
- OpenBugs, 11, 565, 574, *see also* Bugs
- optim(), 405, 413
- optimal design, 455
- options(), 561
- order(), 519
- ordered and unordered categorical outcomes, 119, 123
- ordered logistic model, 119–124
  - fitting in Bugs, 383
  - multilevel, 331–332
  - storable votes, 120–124
- outcome, 37, 251
- outer(), 411
- overdispersion, 21, 114–116, 320

- adjusting standard errors, 115, 117
  - groups in the social network, 338
  - multilevel Poisson model, 335–336, 382, 409–413
  - simulation, 150
  - variance components and, 325
- overlap, *see* causal inference
- pain scores, observed vs. expected, 558
- panel-corrected standard errors, 248
- par(), 305
- parameter expansion, *see* redundant parameters
- parameters saved from Bugs, 350, 356
- partial pooling, 252–259, 394, 477–480
  - Bayesian, 394
  - formula, 253, 258, 269, 477
  - graph, 479
  - group-level predictors and, 269
  - picture, 253
  - plotting data and fitted lines, 257, 266
  - set of regression predictors, 295
  - summarizing a fitted multilevel model, 477–480
- partisan bias, 555
- paste(), 353
- pch, 43
- $p_D$ , effective number of parameters in a Bayesian inference, 525
- phase diagram for decision analysis, 130
- plot(), 43, 350
- plots of replicated datasets, 160, 163
- pmin(), 478
- pnorm(), 404
- points(), 43
- Poisson model, 16, 109–116, 335
  - checking using simulation, 161–163
  - compared to binomial, 112
  - exposure, 111–113
  - interpreting coefficients, 111
  - multilevel, 325–331
  - offset, 326
  - overdispersion, 114–116
  - police stops, 112–116
  - zero-inflated, 126–127
- police stops, 5–6, 21, 112–116, 325–331, 342
  - Bugs model, 382
  - graph, 328
- political ideology, 73
- political party identification, 73–74
- pollution, 76
- polr(), 110, 122
- pooling, *see* complete pooling, no pooling, partial pooling
- pooling factor, 478–480
- posterior distribution
  - picture, 395, 396
  - programming in R, 411
  - social networks model, 409
- posterior predictive checks, 158–165, 513–515
  - data display for dog example, 516, 523
  - numerical summary, 521
  - time plot, 519, 520, 522
  - using Bugs, 518
  - using R, 518
- posterior uncertainty, 149
- postprocessing Bugs output, 359
- poststratification, 178, 181, 206, 301–310
  - formula, 301, 308
  - R code, 308
- potential outcome, 168, 171, 183, 186, 189, 191, 219
  - close substitutes, 171–172
  - interpreting regression coefficients, 34
- pow(), 355
- power calculation, 437–455
  - 2.8 standard errors, 441
  - classical, 439–447
  - general concerns, 439
  - inference for continuous outcomes, 443–447
  - inference for linear regression, 451
  - inference for proportions, 439–443
  - inference for regression coefficients, 446–447
  - inherently speculative, 445, 447
  - multilevel models, 447–454
  - pictures, 440, 441
  - unequal sample sizes, 443
- pre-election polls, 560
- precinct, 325
- predict(), 48, 115, 208, 535
- prediction, 47–49, 68–73
  - Bugs, 361–363
  - interpreting regression coefficients, 34
  - model checking and, 513–515
  - multilevel model, 272–275, 361–363
  - new observations and new groups, 272–275, 361–363
  - nonlinear, 274
- predictive checks, *see* posterior predictive checks
- predictive comparison, 81, 101–104, 167, 168, 466–473, 485
  - comparing models, 472–473
  - formula, 466
  - general approach, 468
  - general notation, 103
  - graph, 467, 468

- interactions and, 103
- model summary, 471
- predictive simulation, 140, 147–151
  - binomial distribution, 149
  - generalized linear models, 148–151
  - latent logistic distribution, 149
  - linear regression, 140–148, 152
  - model checking and, 158–165, 513–524
- predictive standard deviation, 274
- predictive uncertainty, simulation of, 140
- predictors, as distinguished from input variables, 37, 466
- presidential elections, 3–4, 79–84, 294, 301–314, 493, 557, 560
- principal component line, 57
- principles of modeling in Bugs, 366–369
- print(), 350
- prior distribution, 143, 345–348, 413, 427–434
  - Bugs, 354
  - effect on posterior distribution, picture, 430, 432
  - informative, 392–393
    - scale, 430
  - inverse-gamma, why we do not use, 430–434
  - noninformative, 347, 354, 355
  - picture, 395, 396
  - provisional nature of, 347
  - scale, 355
  - uniform, 428–429
  - variance parameters, 432–434, 499–501
  - weakly informative, 431–432
  - Wishart model, 377
- prison sentences, example for predictive comparisons, 470
- probability, *see* distribution
- probability models, simulation of, 137–140
- probability of a tied election, 148
- probit model, 109, 118–119
  - compared to logit, 118, 129
- programming in R, 567
- Progresa, 508–509
- propagating uncertainty, 142, 152
- propensity score matching, *see* causal inference
- provisional nature of prior distributions, 347
- psychological experiment of pilots on flight simulators, 289–290
  
- quantile(), 141, 359
- quasibinomial family, 117
- quasipoisson family, 115
  
- quick tips, 547–549
- R, 10–11, 298, 565, 573
  - abline(), 353, 520
  - apply(), 44, 353, 477
  - array(), 308
  - as.bugs(), 413
  - as.bugs.array(), 400
  - as.vector(), 348
  - attach.bugs(), 305, 352, 358
  - Bayesian inference for social networks model, 409–413
  - brlr package, 104
  - bugs(), 350, 567
  - c(), 350
  - calling Bugs from, 350–352
  - cbind(), 43, 146, 157, 361, 529
  - censored data, 404–408
  - coef(), 43, 156, 260, 267, 280, 352
  - colMeans(), 520
  - colors(), 43
  - colSums(), 411
  - console, 565
  - curve(), 43, 353
  - data.frame(), 48, 140, 452, 535
  - default values in functions, 452
  - digits, 561
  - dim(), 147
  - dimnames(), 400
  - display(), 38–39, 565
  - dnorm(), 404
  - expected(), 123
  - expression(), 148, 353
  - factor(), 255, 349
  - fitted(), 158
  - fixef(), 260, 280
  - function(), 350, 401
  - GAMM package, 567
  - Gibbs sampler, 399–402
    - censored data, 406–408
  - glm(), 79, 110, 565
  - global variables, 400, 412
  - graphics, 562
  - graphics window, 565
  - graphing models fit in Bugs, 352
  - help, 405, 565, 567
  - hett package for robust regression, 110, 124, 133, 567
  - hist(), 137, 536, 562
  - I(), 215, 538
  - ifelse(), 126, 150, 384, 403, 534
  - impute(), 535
  - install.packages(), 567
  - invlogit(), 149
  - jitter.binary(), 89
  - length(), 157

- lgamma(), 411
- library(), 411, 567
- list(), 143, 350
- lm(), 38–39, 402, 565
- lmer(), 259–262, 266, 267, 277, 566, 573
  - limitations, 262, 304, 345
  - logistic regression, 302
  - non-nested model, 289
  - six quick examples, 568–569
  - varying intercepts and slopes, 279–289
- log(), 59
- log10(), 61
- log=TRUE option, 405
- MASS package, 122, 567, 573
- matching(), 208
- Matrix package, 259, 566
- MCMCpack package, 567
- mean(), 56, 359, 477
- mnp package, 110
- mtext(), 520
- mvrnorm(), 143
- NA, 50
- ncol(), 361, 519
- nmatch package, 230
- nrow(), 519
- optim(), 405, 413
- options(), 561
- order(), 519
- outer(), 411
- par(), 305
- paste(), 353
- pch, 43
- plot(), 43, 350
- pmin(), 478
- pnorm(), 404
- points(), 43
- polr(), 110, 122
- predict(), 48, 115, 208, 535
- print(), 350
- probit family, 118
- programming, 567
- quantile(), 141, 359
- quasibinomial family, 117
- quasipoisson family, 115
- R2WinBUGS, 565
- ranef(), 260, 280
- range(), 352, 520
- rbinom(), 137, 149
- read.dta(), 411
- read.table(), 49, 348
- rep(), 452
- replicate(), 139, 147
- replicated data for predictive checking, 518
- return(), 401
- rnegbin(), 150
- rnorm(), 106, 141, 155, 356, 401, 407
- rnorm.trunc(), 407
- rowMeans(), 180
- rowSums(), 147, 411
- rpois(), 150
- runif(), 150, 353, 356
- rwish(), 377
- sample(), 138, 278, 418, 452, 534
- sapply(), 151
- save(), 362
- sd(), 56, 462
- se.coef(), 156, 565
- se.fixef(), 261
- se.ranef(), 261
- sem package, 223
- sigma.hat(), 273, 565
- sim(), 43, 142, 143, 392, 565
- sorting, 519
- subset option in lm() and glm(), 107, 126, 538
- sum(), 147
- summary(), why we don't use, 39
- table(), 353
- tlm(), 124, 133, 567
- tls(), 223
- unique(), 348
- updating functions for Gibbs sampler, 399–402
- var(), 477
- R functions, 44, 139, 147, 151, 404, 534, 535
- $R^2$ , 41, 49, 62, 485
  - adjusted, 475
  - Bayesian definition, 475
  - classical definition, 474
  - computation, 476
  - each level of a model, 474
  - interpretation for model with no constant term, 349
  - multilevel, 473–477
  - pictures, 42
  - why we do not define in terms of model comparison, 474
- R2WinBUGS package, 565
- $\hat{R}$  for summarizing convergence of Bugs fit, 352, 358, 369
- radon, 3, 36, 252–283, 348–369, 480–481
- random effects, 244–246, 259
  - many definitions, 245, 248
  - R, 260
  - superpopulation inferences and, 461
  - why we avoid the term, 2, 245
- random imputation, 534, 537

- randomized experiment, 171–181, 183, *see also* causal inference
- ranef(), 260, 280
- range(), 352, 520
- Rasch model, 315–320
- ratings, 298
- ratio of parameters, 152
- raw (unscaled) parameters, 377
  - compared to adjusted parameters, 423
- rbinom(), 137, 149
- read.dta(), 411
- read.table(), 49, 348
- recall, in social networks survey, 339
- red states and blue states, 310–314
- redundant parameters, 419–427
  - additive, 316, 326, 336, 382, 412, 419–423, 464–466
  - future implementations, 427
  - item-response and ideal-point models, 316
  - multiplicative, 424–427
    - Bugs, 424, 425
  - social network model, 336
- reference condition, in classical no-pooling regression, 349
- reference model, 347
- regression, *see* linear regression, logistic regression, generalized linear models
- regression coefficients, graph, 337, 341
- regression discontinuity, 212–215
- regression to the mean, 57–59
- rejection, not the goal of model checking, 524
- rep(), 452
- repeated measurements, 241–243
  - graph, 450
- replicate(), 139, 147
- replicated data, for predictive checking, 514
- replicated datasets, plotted, 160, 163
- residuals, 40, 97–101
  - binned, 97–101, 559
  - distinguished from errors, 387
  - plot, 47, 48, 97, 114, 558
  - plot vs. predicted values, not vs. observed values, 157, 158
  - social network model, 341–342
  - square root, for Poisson model, 341–342
  - standard deviation of, 41
- return(), 401
- rnegbin(), 150
- rnorm(), 106, 141, 155, 356, 401, 407
- rnorm.trunc(), 407
- robit regression, 124–125, 133, 320
- Bugs, 384
  - generalization of logit and probit, 125
  - latent-data formulation, 384
  - picture, 124
- robust regression, 110, 131
- rodents, 106, 248, 322
- rowMeans(), 180
- rowSums(), 147, 411
- rpois(), 150
- runif(), 150, 353, 356
- rwish(), 377
- S and S-Plus, *see* R
- sample size and interactions, 438
- sample size calculation, 437–455
  - 2.8 standard errors, 441
  - classical, 439–447
  - general concerns, 439
  - inference for continuous outcomes, 443–447
  - inference for linear regression, 451
  - inference for proportions, 439–443
  - inference for regression coefficients, 446–447
  - inherently speculative, 445, 447
  - multilevel models, 447–454
  - pictures, 440, 441
  - unequal sample sizes, 443
- sample(), 138, 278, 418, 452, 534
- sampling, design for, 437–455
- sapply(), 151
- SAS
  - code for matching, 230
  - multilevel modeling in, 570–571
- save(), 362
- scale of prior distribution, 355
- scale-up model for estimation in a social network, 333
- scaled inverse-Wishart distribution, 284–287, 298, 376–380
- Scalia, Antonin, 318
- scaling of predictors, 53
- scatterplot
  - advice, 553–559
  - data and regression lines superimposed, 35
- sd(), 56, 460, 462
- se.coef(), 156, 565
- se.fixef(), 261
- secret weapon, 73–74
  - income and voting, 311
  - pictures, 19, 74, 84
- selection bias, 168, 231, *see also* causal inference
- selection on observables, *see* ignorability
- sem package, 223



- separation in logistic regression, 104, 107
- Sesame Street, 196, 216–220, 231, 509–511
- sex ratio of births, 27, 137–139
- shrinkage and partial pooling, 477
- `sigma.hat()`, 273, 565
- significance, *see* statistical significance
- significant digits and uncertainty, 561
- `sim()`, 43, 142, 143, 392, 565
- simple and complex models, 416
- simulation, 19–20, 137–166
  - combined with analytic calculations, 148
  - comparing simulated to actual data, 158–165
  - compound models, 150–151, 537–538
  - coverage of confidence intervals, 156
  - displaying uncertainty in a fitted model, 149
  - fake data, 50, 155–158
  - generalized linear models, 148–151
  - how many draws are needed, 153
  - logistic regression, 148
  - matrix of simulated parameters and predictions, 146, 149
  - nonlinear predictions, 144–148
  - overdispersed models, 150
  - posterior predictive checks, 158–165, 513–524
  - predictive, 148–151
  - probability models, 137–140
  - regression inferences, 140–148
  - replicated datasets, plotted, 160, 163
  - saved as vectors and matrices, 353, 358
  - why necessary, 141
- slope, *see* varying intercepts and slopes
- small multiples plot, 255, 257, 266, 291, 560
  - logistic regression, 307
- small-area estimation, 301–310
- smoking, 36, 241–243
  - data matrix, 242, 243
- Social Indicators Survey, 529–543
- social networks, 332–342
  - Bayesian inference, 409–413
  - graph of data, 335
  - group sizes, 339
  - predicted from demographics, 337
  - residuals, 341–342
- soft constraint, 257
- software, 565–574, *see also* R, Bugs, Stata, SAS, SPSS, AD Model Builder, HLM, MLWin
  - data and code for examples, 11
  - getting started, 565
  - multilevel modeling, 573
  - S and S-Plus, *see* R
  - WinBugs and OpenBugs, *see* Bugs
- speed dating experiment, 322, 323
- speed of light, 159
- splines, 298
- split-plot latin square, 498–501, 509
- SPSS, multilevel modeling in, 571
- square root transformation, 249, 535
- standard deviation, *see* variance
- standard error, 17, 40
  - picture, 40
  - proportions, 17
- standardizing predictors, 54–57, 96
- Stata
  - multilevel modeling in, 569–570
  - reading in data from, 50, 411
- state-level opinions from national polls, 4–5, 301–310, 493–494
  - Bugs model, 381
- statistical inference, 16–17, 37–42
  - graph of uncertainty, 40, 83
  - measurement error model, 16
  - sampling model, 16
  - standard error, 40, 83
- statistical significance, 42, 69, 83, 94
  - limitations of, 481–484
  - multilevel model, 271
  - problems with, 22–23
  - sample size and power, 440
- stochastic learning in dogs, 515–524
  - Bugs model, 517, 521–524
  - model comparison, 526
- stop and frisk, *see* police stops
- storable votes, 120–124, 331–332, 386
  - Bugs model, 383
  - data and fitted curves, 121
- strategy of debugging, 416
- structural equation modeling, 231
- subclassification, 206–207, 229
- subset option in `lm()` and `glm()`, 107, 126, 538
- subsetting data, 326, 357, 547
  - speeding computation, 418
- sum of squares
  - analysis of variance, 488
  - least squares estimation, 387
- `sum()`, 147
- superpopulation, 167, 173
  - analysis of variance, 491, 500
  - variance, 459–462
    - computing in Bugs, 460
    - graph, 461
- Supreme Court voting, ideal-point model for, 317
- survey design, 437
- survey weighting, 301–310

- switches, 165
- t distribution, 124, 131, 372, 428
- table(), 353
- tables, 563
- teachers, effect of, 459
- teaching evaluations and beauty, 51
- test summary, 513–515
  - graphical, 160, 163, 516, 519, 522, 523
  - numerical, 23, 159, 161, 521
- text editor, 565
- thinning in Bugs, 418, 518
- thresholds, for ordered logit or probit, 119–120
- tied election, probability of, 148
- time series, 297
  - checking a fitted model, 163–165
  - cross-sections, 243–244, 248
- tlm(), 124, 133, 567
- tobit model, 126, 132
- topcoding, for missing-data imputation, 534
- traffic accidents, 110–111
- transformation, 53–77, 548
  - idiosyncratic, 65
  - linear, 53–54
  - logarithmic, 59–65, 98, 252
    - interpreting variance parameters, 327
  - square root, 65, 249, 535
- treatment effect, *see* causal inference
- true values in fake-data simulation, 155, 363
- truncated normal distribution, 407
- tsls(), 223
- twins, 138
- two-factor experiment, 289–290
- two-level classical regression, 240, 248, 270
- two-stage least squares, *see* causal inference, instrumental variables
- two-stage model for mixed discrete/continuous data, 126, 537
- two-way analysis of variance, 495, 496
  
- U.S. Census, 277, 301, 308
- UCLA, 332
- Ulysses, 339
- Umacs, 337, 410–413, 567
- uncertainty, as distinguished from variability, 457–459
- uncontested elections, as missing data, 145
- underdispersion, 21, 22
- unemployment series, graph of data and replications, 163–165
- unexpected patterns, discovering through graphs, 551
- unexplained variance, *see*  $R^2$
- unique(), 348
- units, 37, 251, 553
- unmodeled data and parameters, 364, 367, 378
- unordered categorical regression, 124
- updating functions in R, 399–402
- uranium, as county-level predictor in radon model, 266
- utility theory, 128
  
- validation, 47–49
- validity, 45, 174
- value added by schools, 458–459, 485
- value function, 128
- value of a statistical life, 197
- var(), 477
- variability, as distinguished from uncertainty, 457–459
- variance
  - explained and unexplained, 41, 473–477
  - group level, 270
  - models for, 297
  - multiple error terms, 264
  - non-nested models, 290, 291
  - predictive, 274
  - ratio of between to within, 258
  - residual, 41
  - superpopulation and finite-population, 459–462
- varying intercepts, *see* multilevel model
- varying intercepts and slopes, 1, 237, 279–289, 549
  - Bayesian perspective, 346
  - Bugs, 375–379
  - computing using lmer(), 282
  - graph, 450
  - group-level predictors, 280, 379–380
  - interactions, 282–283
  - logistic regression, 310–314
  - non-nested model, 291
  - notation, 284
  - pictures, 238
- varying slopes without varying intercepts, 283–284
- vector of simulations, 353, 358
- vector-matrix notation, 37–38, 284–287
  - Bugs, 361
- Vietnam War draft lottery, 225–226, 230
- visual and numerical comparisons of replicated to actual data, 164
- voting and income, 79–84, 105, 107, 310–314

- Wald estimate for instrumental variables, 219, 221
- wavelets, 298
- weight
  - age and, 75
  - example of a lognormal distribution, 15
  - height and, 74, 402–408
- weighted average, 19
- weighted least squares, 389
- wells in Bangladesh, 86–92, 105, 193
  - arsenic levels, 90
  - choice models, 127–131
  - map, 87
- when does multilevel modeling make a difference, 247
- WinBugs, *see* Bugs
- WinEdt, 565
- Wishart distribution, 284–287, 298, 376–380
- world wide web connect times, 492–493
- $\chi^2$  test, 25–26, 114
- z-score, 50, 54
- zero-inflated Poisson model, 126–127
- zinc and HIV, 443–447

